

## TYPE 101

Handhonahlen in Kunstharzbindung  
für gehärtetes Material



	Ø	L1	L2	A	E	T	n	Lmax	Körnung
Ohne Schraube	2,00	60	40	11	1	16	3	21	7 - 250
	2,50	60	40	12	1	16	3	20	7 - 250
	3,00	80	60	15	1,5	16	3	37	7 - 250
	3,50	80	60	15	1,5	16	3	37	7 - 250
	4,00	90	65	15	2	16	3	42	7 - 250
	4,50	90	65	15	2	16	3	42	7 - 250
Mit Schraube	5,00	100	75	30	2,5	21	3	34	7 - 250
	6,00	130	100	20	3	21	3	69	7 - 250
	7,00	130	100	20	3	21	3	69	7 - 250
	8,00	140	110	25	4	21	3	74	7 - 250
	9,00	140	110	25	4	21	3	74	7 - 250
	10,00	160	120	25	4,5	21	3	84	7 - 250
	11,00	160	120	25	5	21	4	84	7 - 250
	12,00	160	120	30	5	21	4	79	7 - 250
	13,00	160	120	30	5	21	4	79	7 - 250
	14,00	160	120	30	5	21	4	79	7 - 250
	15,00	160	120	30	6	21	4	79	7 - 250
	16,00	180	140	30	6	21	4	99	7 - 250
	17,00	180	140	30	6	21	4	99	7 - 250
	18,00	180	140	35	6	21	4	94	7 - 250
19,00	180	140	35	6	21	4	94	7 - 250	
20,00	180	140	35	6	21	4	94	7 - 250	

Alle Honwerkzeuge sind um 0,1mm steigend lieferbar + Sonderlängen auf Anfrage

## TYPE 102

Handhonahlen in Kunstharzbindung  
für gehärtetes Material



Ø	L1	L2	A	E	T	n	Lmax	Körnung
5,00	120	95	30	2,5	31	3	49	7 - 250
6,00	130	100	20	3	31	3	64	7 - 250
7,00	130	100	20	3	42	3	59	7 - 250
8,00	140	110	25	4	42	3	64	7 - 250
9,00	140	110	25	4	42	3	64	7 - 250
10,00	160	120	25	4,5	42	3	74	7 - 250
11,00	160	120	25	5	42	4	74	7 - 250
12,00	160	120	30	5	42	4	69	7 - 250
13,00	160	120	30	5	42	4	69	7 - 250
14,00	160	120	30	5	42	4	69	7 - 250
15,00	160	120	30	6	42	4	69	7 - 250
16,00	180	140	30	6	42	4	89	7 - 250
17,00	180	140	30	6	42	4	89	7 - 250
18,00	180	140	35	6	42	4	84	7 - 250
19,00	180	140	35	6	42	4	84	7 - 250
20,00	180	140	35	6	42	4	84	7 - 250

# TYPE 201

**Handhonahlen in Metallbindung**  
für gehärtetes u. weiches Material



	Ø	L1	L2	A	E	T	n	Lmax	Körnung
Ohne Schraube	2,00	60	40	11	1	16	3	21	21
	2,50	60	40	12	1	16	3	20	20
	3,00	80	60	15	1,5	16	3	37	37
	3,50	80	60	15	1,5	16	3	37	37
	4,00	90	65	15	2	16	3	42	42
	4,50	90	65	15	2	16	3	42	42
Mit Schraube	5,00	100	75	30	2,5	21	3	34	34
	6,00	130	100	20	3	21	3	69	69
	7,00	130	100	20	3	21	3	69	69
	8,00	140	110	25	4	21	3	74	74
	9,00	140	110	25	4	21	3	74	74
	10,00	160	120	25	4,5	21	3	84	84
	11,00	160	120	25	5	21	4	84	84
	12,00	160	120	30	5	21	4	79	79
	13,00	160	120	30	5	21	4	79	79
	14,00	160	120	30	5	21	4	79	79
	15,00	160	120	30	6	21	4	79	79
	16,00	180	140	30	6	21	4	99	99
	17,00	180	140	30	6	21	4	99	99
	18,00	180	140	35	6	21	4	94	94
	19,00	180	140	35	6	21	4	94	94
20,00	180	140	35	6	21	4	94	94	

## TYPE 202

**Handhonahlen in Metallbindung**  
für gehärtetes u. weiches Material



Ø	L1	L2	A	E	T	n	Lmax
5,00	120	95	30	2,5	31	3	49
6,00	130	100	20	3	31	3	64
7,00	130	100	20	3	42	3	59
8,00	140	110	25	4	42	3	64
9,00	140	110	25	4	42	3	64
10,00	160	120	25	4,5	42	3	74
11,00	160	120	25	5	42	4	74
12,00	160	120	30	5	42	4	69
13,00	160	120	30	5	42	4	69
14,00	160	120	30	5	42	4	69
15,00	160	120	30	6	42	4	69
16,00	180	140	30	6	42	4	89
17,00	180	140	30	6	42	4	89
18,00	180	140	35	6	42	4	84
19,00	180	140	35	6	42	4	84
20,00	180	140	35	6	42	4	84